



The 2VOICE door entry panel has been designed to be integrated to the IPassan 2-SMART controller for a remote management of your intercom system. With the embedded 2VOICE technology, the door entry panel offers all the benefits of this reliable technology and more. The built-in 2-SMART reader is the gateway between the door entry panel and the iPassan system. The door entry panel is also composed of a camera, a voice synthesis, a 12 buttons brail keypad and an audio system for hearing impaired. The door entry panel is fully DDA compliant.

Main features

- ∞ **Stainless Steel frame material IK08 and IP54**
- ∞ **Camera 120° angle**
- ∞ **Coloured screen 4"**
- ∞ **Built-in sensor detector**
- ∞ **Monobloc electronic for an easy maintenance**
- ∞ **Built-in 2-SMART reader for the integration to the iPassan access control**
- ∞ **Voice messages**
- ∞ **DDA compliant for disabled people**
- ∞ **Vandal resistant door entry panel**

Power Supply

48Vcc provided by the 2VOICE interface 1083/20

Connectivity and System Expansion

The installation of the 2VOICE door entry panel is similar to the others 2VOICE system:

- ∞ **Capability to manage up to 4 automatic switching main door units**
- ∞ **Capability to manage up to 32 columns, each one with 2 secondary call stations**
- ∞ **Capability to manage up to 128 apartment stations for each column with a single power supply unit**
- ∞ **Capability to manage up to 4 apartment stations in parallel for each user**

Communication

The 2-SMART reader inside offer the possibility to connect the panel to the iPassan access control system. It's only necessary to connect this 2-SMART reader to a door of an iPassan controller. The controller offers an automatic detection of the devices.

